




Technical features:

- 10 mm. thick steel front (12 mm. for the 420x550 and 490x620 versions)
- Seals are assembled through automated welding
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special, high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe

Supplied as standard:

- Shelves
- Instruction sheet
- Installation instructions

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight	Pieces	ITEM			
			L	H	P							Type	Dim. Hand	Fin.	Pers. Spec.



- Key only version
- 2 keys item 1.00100.00.2

	260	170	150	10	2	-	8,500	1	1	82010 10 0				
	260	170	200	10	2	-	9,300	1	1	82010 11 0				
*	310	190	150	10	2	1	10,800	1	1	82010 20 0				
*	310	190	200	10	2	1	11,450	1	1	82010 21 0				
	310	190	250	10	2	1	12,400	1	1	82010 22 0				
*	360	240	150	10	2	1	14,550	1	1	82010 30 0				
*	360	240	200	10	2	1	15,200	1	1	82010 31 0				
	360	240	250	10	2	1	16,300	1	1	82010 32 0				
*	420	300	200	10	2	3	21,200	1	1	82010 40 0				
*	420	300	250	10	2	3	22,800	1	1	82010 41 0				
	420	300	300	10	2	3	24,600	1	1	82010 42 0				
*	490	360	200	10	2	3	28,600	1	1	82010 50 0				
*	490	360	250	10	2	3	29,750	1	1	82010 51 0				
	490	360	300	10	2	3	31,300	1	1	82010 52 0				
	300	420	200	10	2	3	22,000	1	1	82010 60 0				
	300	420	250	10	2	3	23,700	1	1	82010 61 0				
	300	420	300	10	2	3	24,700	1	1	82010 62 0				
	360	490	200	10	2	3	29,100	1	1	82010 70 0				
	360	490	250	10	2	3	30,400	1	1	82010 71 0				
	360	490	300	10	2	3	32,400	1	1	82010 72 0				
	420	550	200	12	2	3	39,450	1	1	82010 80 0				
	420	550	250	12	2	3	41,000	1	1	82010 81 0				
	420	550	300	12	2	3	43,300	1	1	82010 82 0				
	420	550	350	12	2	3	44,900	1	1	82010 83 0				
	490	620	200	12	2	3	50,300	1	1	82010 90 0				
	490	620	250	12	2	3	52,400	1	1	82010 91 0				
	490	620	300	12	2	3	54,600	1	1	82010 92 0				