






Technical features:

- Modular front and safe compartment
- 10 mm. thick steel front
- 5 mm. thick steel side and upper walls
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe.
- Opening commands do not protrude when in the rest position

Supplied as standard:

- Frame edge cover
- Shelf
- Bolts for fixing the compartment
- Instruction sheet
- Installation instructions

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight Kg	Pieces	ITEM						
			L	H	P							Type	Dim.	Hand	Fin.	Pers. Spec.		
	<ul style="list-style-type: none"> • Safe compartment with temporary cover 		470	336	200				-	10,650	1	1	83000	40	0			
		*	470	336	250				-	12,000	1	1	83000	41	0			
	<ul style="list-style-type: none"> • Faceplate with key • Two keys item 1.00101.00.2 • To be combined with item 83000.40/41 	*	420	300		10	2	3	1	17,900	1	1	83010	40	0			
	<ul style="list-style-type: none"> • Faceplate with electronic combinator • Internal light • To be combined with item 83000.40/41 • 1.5 V alkaline thin battery operation • Laser welded sealing parts assembly • SUPPLIED AS STANDARD: Power cable • ON REQUEST: Master code function (spec. TF) 		420	300		10	2	3	1	18,300	1	1	83610	40	0			
	<ul style="list-style-type: none"> • Lit keypad • Faceplate with electronic combinator • Internal light • To be combined with item 83000.40/41 • 1.5 V alkaline thin battery operation • Laser welded sealing parts assembly • SUPPLIED AS STANDARD: Power cable 		420	300		10	2	3	1	18,300	1	1	83710	40	0			