



Technical features:

- Zinc plated steel case
- Nickel-plated latch, roller and dead-bolt
- Latch or reversible latch/bolt (where this is provided for)

Hand:

0 = Non-handed

Supplied as standard:

- Set of nylon roses item 1.06012.01.0
- Lock and cylinder fixing screws
- Instruction sheet

Cylinder to be ordered separately


series 08710 or 0E300 (ASIX)

On request:

- Specific striking plates
- Needle key cylinder, series 02400
- Cylinder protective rose item 1.06460.00.0



Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight	Pieces	ITEM				
									Type	Dim.	Hand	Fin.	Pers. Spec.



- Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.

- 10.5 to 16.5 mm. adjustable latch and piston
- Nylon spacers
- 12 V ac CE
- ON REQUEST:
- Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

3	1	85	24	25	3,500	1	1	16425	25	0			
3	1	85	24	30	3,500	1	1	16425	30	0			
3	1	85	24	35	3,500	1	1	16425	35	0			


- Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 1.920 mm.
- lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ac CE
- ON REQUEST:
- Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

3	1	85	24	25	3,380	1	1	16600	25	0			
3	1	85	24	30	3,400	1	1	16600	30	0			
3	1	85	24	35	3,420	1	1	16600	35	0			

- Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 2.300 mm.
- upper adjustment 350 mm.
- lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ac CE
- ON REQUEST:
- Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0


3	1	85	24	25	3,780	1	1	16625	25	0			
3	1	85	24	30	3,800	1	1	16625	30	0			
3	1	85	24	35	3,820	1	1	16625	35	0			

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
									Type	Dim.	Hand	Fin.	Pers.



- Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 3 lateral dead-bolts
- Nylon spacers
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

3	1	-	24	25	3,600	1	1	46420	25	0
3	1	-	24	30	3,620	1	1	46420	30	0
3	1	-	24	35	3,640	1	1	46420	35	0



- Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch and piston
- 3 lateral dead-bolts
- Nylon spacers
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

3	1	85	24	25	3,500	1	1	46425	25	0
3	1	85	24	30	3,500	1	1	46425	30	0
3	1	85	24	35	3,500	1	1	46425	35	0


- Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 1.920 mm.
- lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch
- 3 lateral dead-bolts
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

3	1	85	24	25	3,200	1	1	46600	25	0
3	1	85	24	30	3,220	1	1	46600	30	0
3	1	85	24	35	3,240	1	1	46600	35	0

- Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 2.300 mm.
- upper adjustment 350 mm.
- lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch
- 3 lateral dead-bolts
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0


3	1	85	24	25	3,000	1	1	46625	25	0
3	1	85	24	30	3,000	1	1	46625	30	0
3	1	85	24	35	3,640	1	1	46625	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
									Type	Dim.	Hand	Fin.




- Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch and piston
- 2 lateral dead-bolts
- Top extended bolt
- Nylon spacers
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0

2	1	85	24	25	3,400	1	1	46435	25	0		
2	1	85	24	30	3,420	1	1	46435	30	0		
2	1	85	24	35	3,440	1	1	46435	35	0		




- Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch and piston
- 1 lateral dead-bolt
- Vertical extended bolts
- Nylon spacers
- ON REQUEST:
 - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0
 - Floor striker item 1.06086.00.0
 - Floor striker with sprung dust cover item 1.06086.02.0

1	1	85	24	25	3,500	1	1	46445	25	0		
1	1	85	24	30	3,500	1	1	46445	30	0		
1	1	85	24	35	3,240	1	1	46445	35	0		

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
									Type	Dim.	Hand	Fin.
	<ul style="list-style-type: none"> • Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm. - upper adjustment 650 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts • Nylon spacers • ON REQUEST: <ul style="list-style-type: none"> - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0 - Floor striker item 1.06086.00.0 - Floor striker with sprung dust cover item 1.06086.02.0 	3	1	-	24	25	3,600	1	1	46450	25	0
		3	1	-	24	30	3,500	1	1	46450	30	0
		3	1	-	24	35	3,640	1	1	46450	35	0
	<ul style="list-style-type: none"> • Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 1.920 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts • ON REQUEST: <ul style="list-style-type: none"> - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0 	3	1	-	24	25	3,200	1	1	46605	25	0
		3	1	-	24	30	3,220	1	1	46605	30	0
		3	1	-	24	35	3,240	1	1	46605	35	0
	<ul style="list-style-type: none"> • Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 2.300 mm. - upper adjustment 350 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts • ON REQUEST: <ul style="list-style-type: none"> - Adjustable striking plate item 1.06400.00.0 or item 1.06401.00.0 	3	1	-	24	25	3,600	1	1	46650	25	0
		3	1	-	24	30	3,620	1	1	46650	30	0
		3	1	-	24	35	3,640	1	1	46650	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
									Type	Dim.	Hand	Fin.



- Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ac CE


3	1	85	24	25	3,500	1	1	16525	25	0
3	1	85	24	30	3,500	1	1	16525	30	0
3	1	85	24	35	3,500	1	1	16525	35	0

- Stainless steel adjustable flat faceplate 24 x 7 mm., 1.920 mm.
- lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ac CE

3	1	85	24	25	3,380	1	1	16700	25	0
3	1	85	24	30	3,400	1	1	16700	30	0
3	1	85	24	35	3,420	1	1	16700	35	0

- Stainless steel adjustable flat faceplate 24 x 7 mm., 2.300 mm.
- upper adjustment 350 mm.
- lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ac CE

3	1	85	24	25	3,780	1	1	16725	25	0
3	1	85	24	30	3,800	1	1	16725	30	0
3	1	85	24	35	3,820	1	1	16725	35	0



- Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm.
- upper adjustment 650 mm.
- lower adjustment 150 mm.
- 3 lateral dead-bolts
- Nylon spacers

3	1	-	24	25	3,600	1	1	46520	25	0
3	1	-	24	30	3,620	1	1	46520	30	0
3	1	-	24	35	3,640	1	1	46520	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
									Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> • Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm. - upper adjustment 650 mm. - lower adjustment 150 mm. • 11 to 17 mm. adjustable latch • 3 lateral dead-bolts • Nylon spacers 	3	1	85	24	25	3,600	1	1	46525	25	0	
		3	1	85	24	30	3,500	1	1	46525	30	0	
		3	1	85	24	35	3,500	1	1	46525	35	0	
	<ul style="list-style-type: none"> • Stainless steel adjustable flat faceplate 24 x 3 mm., 1.920 mm. - lower adjustment 150 mm. • 11 to 17 mm. adjustable latch • 3 lateral dead-bolts 	3	1	85	24	25	3,200	1	1	46700	25	0	
		3	1	85	24	30	3,220	1	1	46700	30	0	
		3	1	85	24	35	3,240	1	1	46700	35	0	
	<ul style="list-style-type: none"> • Stainless steel adjustable flat faceplate 24 x 3 mm., 2.300 mm. - upper adjustment 350 mm. - lower adjustment 150 mm. • 11 to 17 mm. adjustable latch • 3 lateral dead-bolts 	3	1	85	24	25	3,600	1	1	46725	25	0	
		3	1	85	24	30	3,620	1	1	46725	30	0	
		3	1	85	24	35	3,640	1	1	46725	35	0	

	<ul style="list-style-type: none"> • Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm. - upper adjustment 650 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts • Nylon spacers 	3	1	-	24	25	3,500	1	1	46550	25	0
		3	1	-	24	30	3,500	1	1	46550	30	0
		3	1	-	24	35	3,500	1	1	46550	35	0
	<ul style="list-style-type: none"> • Stainless steel adjustable flat faceplate 24 x 3 mm., 1.920 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts 	3	1	-	24	25	3,200	1	1	46705	25	0
		3	1	-	24	30	3,220	1	1	46705	30	0
		3	1	-	24	35	3,240	1	1	46705	35	0
	<ul style="list-style-type: none"> • Stainless steel adjustable flat faceplate 24 x 3 mm., 2.300 mm. - upper adjustment 350 mm. - lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts 	3	1	-	24	25	3,600	1	1	46750	25	0
		3	1	-	24	30	3,620	1	1	46750	30	0
		3	1	-	24	35	3,640	1	1	46750	35	0