



Technical features:

- 10 mm. thick steel front
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special, high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe.
- Opening commands do not protrude when in the rest position


Supplied as standard:

- Power cable
- Shelves
- Fixing grips (4 pieces)
- Use and maintenance instructions
- Installation instructions

On request:

- Safes with master code function (caratt. TF)

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Kg	Pieces	ITEM				
			L	H	P							Type	Dim.	Hand	Fin.	Pers.



- Electronic combinator
- Internal light
- 1.5 V alkaline thin battery operation
- Removable door
- Laser welded sealing parts assembly

	360	240	300	10	2	1	28,200	1	1	82650	34 0					
	420	300	350	10	2	3	40,500	1	1	82650	43 0					
	490	360	350	10	2	3	51,000	1	1	82650	53 0					
*	360	490	400	10	2	3	55,650	1	1	82650	74 0					

TO BE DISCONTINUED